

TECHNICAL DATA SHEET

RAYCO PREMIUM SKIMCOAT PASTE TYPE - READY TO USE is a skim coat smoothing compound, a white paste designed for leveling uneven or rough surfaces and filling minor surface voids. It effectively addresses exposed aggregates and hairline cracks in general rendering. Suitable for both exterior and interior applications, it provides a beautifully smooth, natural white finish

PRODUCT FEATURES:

- Ready-to-use paste
- Achieves a flawlessly smooth white finish
- Can be utilized as a decorative topcoat without need for painting, or can be painted over with or without primer
- Excellent trowelability
- Suitable for application with a spray machine to create a textured, rough surface
- UV resistant
- Saves both time and money (less paint may be needed)

AREAS OF APPLICATION

- Walls and ceilings
- Interior and exterior applications.

PRODUCT DATA

Color	: White
Coverage	: Coverage: 20–25 m ² per 20 kg pail at 1 mm thickness; practical coverage may vary
Packaging	: 5kg pail, 20kg pail
Storage	: Store in a cool, dry place, away from direct sunlight
Shelf Life	: 12 months from manufacturing date

SURFACE PREPARATION

Apply the first coat using a stainless steel trowel or spray equipment. A minimum of two coats is required to achieve a satisfactory surface. Allow 10–30 minutes drying time before applying the second coat to ensure the first coat is not drawn off when applying the second coat. Once the second coat is applied, use sandpaper to achieve a smooth finish. Allow a curing time of 24 hours before applying any covering material, such as paint or wallpaper.

MIXING

Pre-mixed paste that requires no water addition.

HEALTH AND SAFETY

The product is non-toxic but alkaline in nature. A dust mask should be used when handling Rayco Premium Skimcoat Ready-to-use. Gloves should be worn during application. Refer to Material Safety Data Sheet for more information on Health and Safety.

WARRANTY

Due to different methods of applications, and the various properties of surfaces, we cannot assume responsibility or liability with regards to the application of our products. Our guarantee and liability are restricted to the quality of our products at the time of acceptance of the customer of such products. In no case, shall our liability extend beyond replacement of defective products, if any, found at the time of acceptance. For all deliveries and services, our General Sales Condition including warranties stipulated for each case is valid