

## TECHNICAL DATA SHEET

**RAYCOAT ACRYPRIME** serves as a preparatory coating applied to floor surfaces before installing waterproofing membranes and wall-casting systems.

### PRODUCT FEATURES

- Minimizes dust generation and enhances the substrate's resistance to wear
- Effectively seals open pores in rough, absorbent concrete to impede moisture penetration and the formation of blisters.
- Optimizes bonding properties for subsequent application of waterproofing membranes.



### PRODUCT DATA

Coverage	: 120 - 150 m <sup>2</sup> per coating
Drying Time	: Dries within 1 to 4 hours, influenced by surface type, temperature, and humidity levels. Subsequent coats can be applied once the product is dry to the touch.
Packaging	: 4L pail, 20L pail
Storage	: Shelf life is 12 months if stored in the original unopened container
Before Application Color	: Milky White
After Application Color	: Clear

### SURFACE PREPARATION

The substrate must be clean, structurally sound, free of dust and contaminants such as oil, laitance, curing compounds, wax, grease, or paint. Additionally, it must comply with current building codes and have cured for at least 28 days

### PRECAUTIONS

Temperature range of use: 10°C to 45°C. The primer must be covered within 24 hours. Clean tools and equipment with water before product dries

### PRODUCT PREPARATION

- No mixing required. Stir the product in the pail prior to use and then apply an even coat using a brush or roller.
- Apply 1-2 coats of Raycoat Acryprime
- Allow 1-4 hours curing time before applying the topcoat

### WARRANTY

Due to different methods of applications, and the various properties of surfaces, we cannot assume responsibility or liability with regards to the application of our products. Our guarantee and liability are restricted to the quality of our products at the time of acceptance of the customer of such products. In no case, shall our liability extend beyond replacement of defective products, if any, found at the time of acceptance. For all deliveries and services, our General Sales Condition including warranties stipulated for each case is valid.

